

Made in Baden-Württemberg

Our draining trolleys are the result of our total commitment to quality, innovative technology, years of experience and consistent further development of tried and tested systems.

DRAINING TROLLEY

AW 300 DL | Compressed air

Typ AW 300 DL:

Large filter surface 420 X 970 mm

equivalent to 0.4 m²

Length 1500 mm

Width 500 mm

Height 1200 mm

Weight with accessories 200 kg

Capacity 300 l





DRAINING TROLLEY

AW 300 DL | Compressed air



Double perforated insert

- 1 5 mm Ø
- 1 Fine separation with 0,5 mm Ø



Cock 2" for tank cleaning



Sturdy chip chute



Accessories

- 1 Suction hose 2" x 3 m
- 1 Discharge hose 1 1/4" x 3 m
- 1 Compressed air hose 9 x 8 m nominal size
- 1 Round nozzle 50 mm inside with
- 1 Round nozzle 16 mm inside with
- 1 Flat nozzle 150 mm wide
- 1 Chip pusher



Air operated suction unit with high-performance silencer

- Air consumption: 900 l/min
- Negative pressure: 0.2 bar
- Optimal air connection: 6 bar
- Suction capacity with clean filter: 200 l/min
- pump: 230 V, 50 Hz, 3.93 A
- H max. 8.6 m Q min. 100 l/min
- H min. 3.8 m Q max. 250 l/min